ALL AMERICAN DESIGNER SERIES

2012 STANDARD SPECIFICATIONS (Dyersville)

Effective January 1, 2012

FLOORS & CEILING

2" x 8" Floor joists & Triple Center Beam @ 16" o.c. (24' wide plans) 2" x 10" Floor joists & Triple Center Beam @ 16" o.c. (28' wide plans) 2" x 12" Floor joists & Triple Center Beam @ 16" o.c. (32' wide plans)

Double Rim Joists at eave sides of house

Construction adhesive and mechanical fasteners - subfloor to floor joist 5/8" Tongue and groove oriented strand board subfloor or equivalent

2"x6" Ceiling and box joists (Two Story plans)

5/8" Type-X gypsum drywall - glued to trusses 8' First floor ceilings (9' on select Two Story plans)

8' Second floor ceilings (All Two Story plans) Stomped Textured finish ceiling

ROOF
30 PSF ground snow load rating

24" O.C. roof trusses

Ranch - 6/12 roof pitch (multi-section per plan)

Std cape: 12/12 roof pitch

7/16" oriented strand board or equal sheathing

15# roof felt underpayment

Certainteed 30 Year architectural laminate shingles - nailed

14" Overhang with vented Vinyl soffit system

2" x 6" fascia with Aluminum Cover

Ice damming protection (where required)

Continuous Ridge Vent

EXTERIOR WALLS & INSULATION

2" x 6" studs - 16" o.c.

2" x 6" plates - double top plate / single plate at bottom and gable end walls

7/16" Oriented strand board or equivalent

Certainteed Newtown vinyl siding

Tyvek House wrap

Blown Cellulose (R-38) - Ranch & 2 Story - Ceiling Condensed Fiberglass (R-30) - Capes - Ceiling

Fiberglass Batt (R-19) - Exterior Walls

Vapor Barrier Wall Finish

INTERIOR WALLS

2" x 4" studs - 16" o.c.

2" x 4" top and bottom plates

1/2" gypsum drywall

Sherwin Williams Latex Paint - Duck White

Rounded wall corners

Orange Peel Wall Texture

MARRIAGE WALLS

2" x 3" Studs - 16" O.C. per plan (2"x4" studs on select plans)

2" x 3" plates - double top, single bottom

7/16" oriented strand board or equivalent

WINDOWS & DOORS

Ply-Gem Single hung vinyl (Low-E) windows w/screens - tilt sash

Ply-Gem Sliding patio door (select plans)

Taylor - 1-3/4" thick Steel insulated entry doors - Exterior

Brushed nickel entry knob - Exterior

6 Panel molded doors - Interior

Brushed nickel knob door handles - Interior

Pre-finished Oak trim at windows, doors and base boards

PLUMBING

Pex water lines - thru floor drop PVC drainage system - thru floor drop Exterior water spigot - shipped loose

Washer and dryer hookup

Plumbing Vent for Future Basement Bath

FLOOR COVERING

Vinyl Madera flooring - Kitchen, bath and utility areas

Carpet flooring - Dining, living and bedrooms - Shaw Install Program

Carpet pad - 6 pound

KITCHEN

Merillat Basics cabinetry

8" Deep stainless steel sink

Ventless range hood

Wilsonart laminated countertop with 4" Backsplash

Peerless Chrome faucet w/ sprayer

Fan/light combination exhaust vent - vented to eaves or gables

Mirror(s)

Vanity light bar(s)

Merillat Basics vanity

Wilsonart laminate countertop with China sink(s) & 4" Backsplash

One piece fiberglass tub and/or shower combination -Per Plan

Round front porcelain water closet

Peerless Chrome Double lever faucet(s)

Chrome Toilet paper and towel holders

Anti-Scald Shower Faucets

LIGHTING

Reinforced switched ceiling box - all bedrooms and living room

Eyeball can light - Above kitchen sink

Chandelier - Dining room

Dome light - Breakfast nook

Dome light - Utility room

Dome light - Hall

Dome light - Walk-in closet

Dome light - Basement stairway

Coach lamp - Front and rear/side entrance

ELECTRICAL

200 Amp 40 Slot entrance panel - Cutler Hammer

Arc-fault protected bedrooms

12-2 Copper wiring or Better

Doorbell - Front entrance

Television Box & Pull-wire (3) Phone Jacks - Cat 5 (1)

Dual Sensor Smoke detectors - where applicable

CO / Smoke detectors - where applicable

Pre-wired for basement smoke detectors if applicable (field installed by others)

Stove Receptical

Dryer Receptical

Energy Star Rated CFL Bulbs Included

GFCI Protected Outlets - Exterior Front and Rear of Home

GFCI Protected Outlets - Kitchens and Baths

Miscellaneous

Wire Closet Shelving

1 Year General Warranty and 10 Year Structural

**Note: Specifications subject to change without notice.

Revised: November 1, 2011